


$\leq$ 

 $\equiv$ 

 $\geq$ 

1. Staniš B., Tubiš V., Čelar, N. (2011). Straight Lane Saturation Flow and Its Rate in Serbian Cities, - Transport, vol. 26, pp. 329-334 (IF2012=1.081) DOI: [10.3846/16484142.2011.623762](https://doi.org/10.3846/16484142.2011.623762), ISSN 1648-4142
2. Staniš B., Tubiš V., Čelar, N. (2011). Design and evaluation of a grade-separated intersection: a case study of the proposed Belgrade 'Hipodrom, - Transportation Planning and Technology, vol. 34, pp. 625-636, (IF2011=0.203), DOI: 10.1080/03081060.2011.600096, ISSN: 0308-1060
3. Čelar, N., Kajališ J., Stankoviš S. and Stepanoviš N. (2018) "Methodology for control delay estimation using new algorithm for critical points identification", *Journal of Transportation Engineering Part A: Systems*, 144(2), pp. 1-8, (IF2018=0.641) DOI: 10.1061/JTEPBS.0000110, ISSN: 2473-2907
4. Kajališ J., Čelar, N. and Stankoviš S. (2018) "Travel time estimation on urban street segment", *Promet - Traffic & Transportation*, 30(1), pp. 115-120, (IF2018=0.768) DOI: 10.7307/ptt.v30i1.2473, ISSN: 0353-5320
5. Stankoviš S., Čelar, N., Kajališ J. and Vukiševiš Biševac, I. (2020) "Micro and macro approach to modeling relationship between control and stopped delay at signalized intersections", *Journal of Transportation Engineering Part A: Systems*, 146(1), pp. 1-19, (IF2018=0.641) DOI: 10.1061/JTEPBS.0000288, ISSN: 2473-2907

ДЕКАН ФАКУЛТЕТА